



TMI (HK) LIMITED



Shenzhen KONETIKI Industrial Co.,Ltd.

Tel: +86 755 3367 4665 | 24Hrs : +86 18 123 90 8684
 Email: info@konetiki.com | Web: www.konetiki.com

Add: F7, Building 1, Yongqi industrial estate, Xixiang, Bao'an Shenzhen, China



20W LED

 	Integrated Solar Street Light		Mounting height:5-6M	
	Solar panel	Max Power	18V 25W (high efficiency solar panel)	
		Life Time	25 years	
	Battery	Type	Lithium battery 120WH	
		Life Time	3-5 years	
	Led lamp (with sensor)	Led chip brand	Bridgelux 3030 30pcs	
		Lumen(LM)	2000-2200	
		Life Time	50000 hours	
		Color Temperature(CCT)	6000K-6500K	
	Lamps material of main body	Aluminium Alloy, anti-corrosion and waterproof		
	Color of main body	Black, silver		
	Working modes	Motion sensor, time control, motion sensor+time control. It can be switched by a remote control		
	Charge time	8 hours (by sun)		
	Discharge time	12 hours, 5-7 backup days		
	Certificate	CE/ROHS/TUV-IP66		
Warranty period	2 years for the full system			
Packing & Weight	Product Size	536*355*77mm		
	Product Weight	5.6KG		
	Carton Size	610*430*130mm		
	GW.for Carton	7KG		
	Quantity/Carton	1set/carton		
Packs Containers	20GP	800pcs		
	40GP	1660pcs		
1.This offer is only EXW price,does not include shipping cost. 2.More quantity more discount. 3.Payment Terms:T/T or Western Union prepaid before shipment 4.Quotation validity: 20 days.				



We guarantee everything we sell!



TMI (HK) LIMITED

Shenzhen KONETIKI Industrial Co.,Ltd.

Tel: +86 755 3367 4665 | 24Hrs : +86 18 123 90 8684
 Email: info@konetiki.com | Web: www.konetiki.com
 Add: F7, Building 1, Yongqi industrial estate, Xixiang, Bao'an Shenzhen, China

30W LED

	Integrated Solar Street Light		Mounting height:6-7M
	Solar panel	Max Power	18V 30W (high efficiency solar panel)
		Life Time	25 years
	Battery	Type	Lithium battery 145WH
		Life Time	3-5 years
	Led lamp (with sensor)	Led chip brand	Bridgelux 3030 60PCS
		Lumen(LM)	3000-3400
		Life Time	50000 hours
		Color Temperature(CCT)	6000K-6500K
	Lamps material of main body	Aluminium Alloy, anti-corrosion and waterproof	
	Color of main body	Black, silver	
	Working modes	Motion sensor, time control, motion sensor+time control. It can be switched by a remote control	
	Charge time	8 hours (by sun)	
	Discharge time	12 hours, 5-7 backup days	
	Certificate	CE/ROHS/TUV-IP66	
Warranty period	2 years for the full system		
Packing & Weight	Product Size	605*355*156mm	
	Product Weight	6.7KG	
	Carton Size	690*415*135mm	
	GW.for Carton	8KG	
	Quantity/Carton	1set/carton	
Packs Containers	20GP	730pcs	
	40GP	1510pcs	
			
1.This offer is only EXW price,does not include shipping cost. 2.More quantity more discount. 3.Payment Terms:T/T or Western Union prepaid before shipment 4.Quotation validity: 20 days.			



TMI (HK) LIMITED

Shenzhen KONETIKI Industrial Co.,Ltd.

Tel: +86 755 3367 4665 | 24Hrs : +86 18 123 90 8684

Email: info@konetiki.com | Web: www.konetiki.com

Add: F7, Building 1, Yongqi industrial estate, Xixiang, Bao'an Shenzhen, China



40W LED



Integrated Solar Street Light		Mounting height:6-7M
Solar panel	Max Power	18V 45W (high efficiency solar panel)
	Life Time	25 years
Battery	Type	Lithium battery180WH
	Life Time	3-5 years
Led lamp (with sensor)	Led chip brand	Bridgelux 3030 60PCS
	Lumen(LM)	4000-4400
	Life Time	50000 hours
	Color Temperature(CCT)	6000K-6500K
Lamps material of main body	Aluminium Alloy, anti-corrosion and waterproof	
Color of main body	Black, silver	
Working modes	Motion sensor, time control, motion sensor+time control. It can be switched by a remote control	
Charge time	8 hours (by sun)	
Discharge time	12 hours, 5-7 backup days	
Certificate	CE/ROHS/TUV-IP66	
Warranty period	2 years for the full system	
Packing & Weight	Product Size	714*355*144mm
	Product Weight	9.8KG
	Carton Size	790*400*240mm
	GW.for Carton	10.5KG
	Quantity/Carton	1set/carton
Packs Containers	20GP	395pcs
	40GP	825pcs

- 1.This offer is only EXW price,does not include shipping cost.
- 2.More quantity more discount.
- 3.Payment Terms:T/T or Western Union prepaid before shipment
- 4.Quotation validity: 20 days.



We guarantee everything we sell!



TMI (HK) LIMITED

Shenzhen KONETIKI Industrial Co.,Ltd.

Tel: +86 755 3367 4665 | 24Hrs : +86 18 123 90 8684

Email: info@konetiki.com | Web: www.konetiki.com

Add: F7, Building 1, Yongqi industrial estate, Xixiang, Bao'an Shenzhen, China

60W LED



Integrated Solar Street Light		Mounting height:7-8M
Solar panel	Max Power	18V 60W (high efficiency solar panel)
	Life Time	25 years
Battery	Type	Lithium battery 240WH
	Life Time	3-5 years
Led lamp (with sensor)	Led chip brand	Bridgelux 3030 90pcs
	Lumen(LM)	6000-6600
	Life Time	50000 hours
	Color Temperature(CCT)	6000K-6500K
Lamps material of main body	Aluminium Alloy, anti-corrosion and waterproof	
Color of main body	Black, silver	
Working modes	Motion sensor, time control, motion sensor+time control. It can be switched by a remote control	
Charge time	8 hours (by sun)	
Discharge time	12 hours, 5-7 backup days	
Certificate	CE/ROHS/TUV-IP66	
Warranty period	2 years for the full system	
Packing & Weight	Product Size	834*355*162mm
	Product Weight	12KG
	Carton Size	910*430*240mm
	GW.for Carton	13KG
	Quantity/Carton	1set/carton
Packs Containers	20GP	320pcs
	40GP	666pcs

- 1.This offer is only EXW price,does not include shipping cost.
- 2.More quantity more discount.
- 3.Payment Terms:T/T or Western Union prepaid before shipment
- 4.Quotation validity: 20 days.



We guarantee everything we sell!



TMI (HK) LIMITED

Shenzhen KONETIKI Industrial Co.,Ltd.

Tel: +86 755 3367 4665 | 24Hrs : +86 18 123 90 8684
 Email: info@konetiki.com | Web: www.konetiki.com
 Add: F7, Building 1, Yongqi industrial estate, Xixiang, Bao'an Shenzhen, China

80W LED



Integrated Solar Street Light		Mounting height:8-10M
Solar panel	Max Power	18V 72W (high efficiency solar panel)
	Life Time	25 years
Battery	Type	Lithium battery 308WH
	Life Time	3-5 years
Led lamp(with sensor)	Led chip brand	Bridgelux 3030 120PCS
	Lumen(LM)	8000-8800
	Life Time	50000 hours
	Color Temperature(CCT)	6000K-6500K
Lamps material of main body	Aluminium Alloy, anti-corrosion and waterproof	
Color of main body	Black, silver	
Working modes	Motion sensor, time control, motion sensor+time control. It can be switched by a remote control	
Charge time	8 hours (by sun)	
Discharge time	12 hours, 5-7 backup days	
Certificate	CE/ROHS/TUV-IP66	
Warranty period	2 years for the full system	
Packing & Weight	Product Size	1088*355*162mm
	Product Weight	13KG
	Carton Size	1120*430*240mm
	GW.for Carton	14.5KG
	Quantity/Carton	1set/carton
Packs Containers	20GP	270pcs
	40GP	560pcs

- 1.This offer is only EXW price,does not include shipping cost.
- 2.More quantity more discount.
- 3.Payment Terms:T/T or Western Union prepaid before shipment
- 4.Quotation validity: 20 days.



We guarantee everything we sell!



TMI (HK) LIMITED



Shenzhen KONETIKI Industrial Co.,Ltd.

Tel: +86 755 3367 4665 | 24Hrs : +86 18 123 90 8684



Email: info@konetiki.com | Web: www.konetiki.com

Add: F7, Building 1, Yongqi industrial estate, Xixiang, Bao'an Shenzhen, China

100W LED

	Integrated Solar Street Light		Mounting height:8-10M
	Solar panel	Max Power	18V 90W (high efficiency solar panel)
Battery	Life Time	25 years	
	Type	Lithium battery 384WH	
Led lamp (with sensor)	Life Time	3-5 years	
	Led chip brand	USA Bridgelux 3030 150PCS	
	Lumen(LM)	11000-12000	
Lamps material of main body	Life Time	50000 hours	
	Color Temperature(CCT)	6000K-7000K	
Color of main body	Aluminium Alloy, anti-corrosion and waterproof		
Working modes	Black, silver		
Charge time	Motion sensor, time control, motion sensor+time control. It can be switched by a remote control		
Discharge time	8 hours (by sun)		
Certificate	12 hours, 5-7 backup days		
Warranty period	CE/ROHS/TUV-IP66		
Packing & Weight	Product Size	2 years for the full system	
	Product Weight	1263*353*162mm	
	Carton Size	14.3KG	
	GW.for Carton	1280*420*230mm	
	Quantity/Carton	16.5KG	
Packs Containers	20GP	1set/carton	
	40GP	250pcs	
	500pcs		<p>1.This offer is only EXW price,does not include shipping cost. 2.More quantity more discount. 3.Payment Terms:T/T or Western Union prepaid before shipment 4.Quotation validity: 20 days.</p>

120W LED

	Integrated Solar Street Light		Mounting height:10-12M
	Solar panel	Max Power	36V 110W (high efficiency solar panel)
		Life Time	25 years
	Battery	Type	Lithium battery 460WH
		Life Time	3-5 years
	Led lamp (with sensor)	Led chip brand	USA Bridgelux 3030 180PCS
Lumen(LM)		11000-12000	
Life Time		50000 hours	
	Color Temperature(CCT)	6000K-7000K	
	Lamps material of main body	Aluminium Alloy, anti-corrosion and waterproof	
	Color of main body	Black, silver	
	Working modes	Motion sensor, time control, motion sensor+time control. It can be switched by a remote control	
	Charge time	8 hours (by sun)	
	Discharge time	12 hours, 5-7 backup days	
	Certificate	CE/ROHS/TUV-IP66	
	Warranty period	2 years for the full system	
	Packing & Weight	Product Size	1298*600*162mm
		Product Weight	15.7KG
		Carton Size	1358*670*230mm
		GW.for Carton	18.3KG
		Quantity/Carton	1set/carton
Packs Containers	20GP	250pcs	
	40GP	500pcs	
1.This offer is only EXW price,does not include shipping cost. 2.More quantity more discount. 3.Payment Terms:T/T or Western Union prepaid before shipment 4.Quotation validity: 20 days.			

Features of this series solar lights

1. Multi working modes switched by a remote controller.

Multi-mode intelligent controller: Timer / PIR / Timer+PIR. You can choose the best working mode by yourself according to the specific installation situation through remote control.

2. Adjustable angle range: 15°-45°

The angle of the lamp can be adjusted according to the actual installation needs.

There are 3 adjustment holes on the base, you can fix the suitable angle by fixing the corresponding screw hole.

3. Bridgelux 3030 lamp beads.

Ultra high luminous efficiency, designed by the advanced polarizing lens optical system including optical lens patented technology so the led light energy is reasonably and effectively controlled within the required range. Greatly improve the utilization and evenness of light. The whole light utilization rate is above 90%. It will not bring visual interference to drivers, so as to improve driving safety and visual comfort.

4. New high-tech electronic switch.

Using new high-tech electronic switch to improve the stability and decrease the switch failure.

5. Independent battery box design.

IP65 waterproof design for the full system and the independent battery box, increased the waterproof grade and life span. Improved the high temperature insulation effect

6. Professional optical design

150°x 70° meet the road lighting standards.

7. Using advanced stoving varnish process, beautiful look and anti-corrosion.

8. Designed by specialized senior experts, greater conversion efficiency and more stable quality.