







Model	Picture	Parameters	Packing
KT9024		1.Body material: die-casting aluminum 2.Solar Panel: 5V/40W 3.Battery: LiFEPO4 3.2V/30AH 4.WorkingTemperature:-35° - 60° 5.LED: Osram3030*24pcs 6.Temp color: 6000K-6500K 7.Rainy/Cloudy working: 5 days 8.Warranty: 5 years 9.Controller: PWM controller 10.Working time: 8hrs/10hrs/2hrs 11.LEW Power: LED24W 12. Light distribution: light distribution of batwing street lamp 13.Amounting height: 4-5m	1.Lamp size: 610*200*390mm 2.Solar Panelsize:540*515*30mm 3.Lamp Carton: 700*280*460mm 4.Solar Panel Carton: 590*580*80mm
KT9048		1.Body material: die-casting aluminum 2.Solar Panel: 5V/50W 3.Battery: LiFEPO4 3.2V/40AH 4.WorkingTemperature:-35° - 60° 5.LED: Osram3030*48pcs 6.Temp color: 6000K-6500K 7.Rainy/Cloudy working: 5 days 8.Warranty: 5 years 9.Controller: PWM controller 10.Working time: 8hrs/10hrs/2hrs 11.LEW Power: LED48W 12. Light distribution: light distribution of batwing street lamp 13.Amounting height: 6-8m	1.Lamp size: 610*200*390mm 2.Solar Panelsize:695*515*30mm 3.Lamp Carton: 700*280*460mm 4.Solar Panel Carton: 740*580*80mm
KT9076		1.Body material: die-casting aluminum 2.Solar Panel: 5V/60W 3.Battery: LiFEPO4 3.2V/60AH 4.WorkingTemperature:-35° - 60° 5.LED: 2835*76pcs 6.Temp color: 6000K-6500K 7.Rainy/Cloudy working: 5 days 8.Warranty: 5 years 9.Controller: PWM controller 10.Working time: 8hrs/10hrs/2hrs 11.LEW Power: LED76W 12. Light distribution: light distribution of batwing street lamp 13.Amounting height: 6-8m	1.Lamp size: 610*200*390mm 2.Solar Panelsize:825*515*30mm 3.Lamp Carton: 700*280*460mm 4.Solar Panel Carton: 870*580*80mm

KT9024S		<p>1.Body material: die-casting aluminum 2.Solar Panel: 5V/40W 3.Battery: LiFEPO4 3.2V/30AH 4.WorkingTemperature:-35° - 60° 5.LED: Osram3030*24pcs 6.Temp color: 6000K-6500K 7.Rainy/Cloudy working: 5 days 8.Warranty: 5 years 9.Controller: PWM controller 10.Working time: 8hrs/10hrs/2hrs 11.LEW Power: LED24W 12. Light distribution: light distribution of batwing street lamp 13.Amounting height: 4-5m</p>	<p>1.Lamp size: 610*200*80mm 2.Solar Panelsize:540*515*30mm 3.Lamp Carton: 640*265*120mm 4.Solar Panel Carton: 590*580*80mm</p>
KT9048S		<p>1.Body material: die-casting aluminum 2.Solar Panel: 5V/50W 3.Battery: LiFEPO4 3.2V/40AH 4.WorkingTemperature:-35° - 60° 5.LED: Osram3030*48pcs 6.Temp color: 6000K-6500K 7.Rainy/Cloudy working: 5 days 8.Warranty: 5 years 9.Controller: PWM controller/8h 10.LEW Power: LED48W 11. Light distribution: light distribution of batwing street lamp 12.Amounting height: 5-6m</p>	<p>1.Lamp size: 610*200*80mm 2.Solar Panelsize:695*515*30mm 3.Lamp Carton: 640*265*120mm 4.Solar Panel Carton: 740*580*80mm</p>
KT9076S		<p>1.Body material: die-casting aluminum 2.Solar Panel: 5V/60W 3.Battery: LiFEPO4 3.2V/60AH 4.WorkingTemperature:-35° - 60° 5.LED: 2835*76pcs 6.Temp color: 6000K-6500K 7.Rainy/Cloudy working: 5 days 8.Warranty: 5 years 9.Controller: PWM controller 10.Working time: 8hrs/10hrs/2hrs 11.LEW Power: LED76W 12. Light distribution: light distribution of batwing street lamp 13.Amounting height: 6-8m</p>	<p>1.Lamp size: 610*200*80mm 2.Solar Panelsize:825*515*30mm 3.Lamp Carton: 640*265*120mm 4.Solar Panel Carton: 870*580*80mm</p>